This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.


Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.


As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

Self Ordered Magnetic Array (SOMA) Patterned Media





Potential Density Gain



0.4

0.5

0.3

0.2

area fraction

0.1

9.0

D. Weller and M. Doerner, Annu. Rev. Mat. Sci 2000, 30: 611-644

A/A_m


0.5

SEAGATE CONFIDENTIAL Seagate Research.ppt

Seagate.

Information the way you want it.

Synthesis




Seagate.
Information the way you want it...

SEAGATE CONFIDENTIAL Seagate Research.ppt (

Chemically Synthesized Nanoparticle Arrays

4 nm FePt particles




S. Sun et al., Science 287, 1989 (2000)

Seagate.

Information the way you want it.

SEAGATE CONFIDENTIAL Seagate Research.ppt

Chemically Synthesized Nanoparticle Arrays



4 nm Fe₅₂Pt₄₈

 $\xi \sim 100 - 1000 \text{ nm}$ coherence length

S. Sun et al., Science 287, 1989 (2000)

SEAGATE CONFIDENTIAL Seagate Research.ppt

Seagate.
Information the way you want it...

Critical Issues / Challenges

FABRICATION - PROPERTY CONTROL

- Nanoparticle Fabrication
- Control of Size Property Distribution / Uniformity
- Control of Interparticle Interactions
- Deposition on Flat Smooth Surface Roughness Control
- Control of Magnetization Dispersion Texturing
- Control of Large Scale Ordering

RECORDING

- Writeability (Write Coercivity Constraint)
- Addressability (rotating disk vs xy stage)
- SNR requirements (read back sensor, noise)
- Magnetic Interactions (demagnetization)
- Stability



Information the way you want it...


SEAGATE CONFIDENTIAL

SOMA Seagate Approach

1. Pattern Writer, 257 nm UV




2. After Resist Removal



with Nanoparticles 4. Planarization



glass ceramic, Si, ... $Ra \equiv 0.4-0.5nm$ 15 - 20 nm



(D. Weller, N. Deeman, Th. Valet, N. Shukla, R. van de Veerdonk)


SEAGATE CONFIDENTIAL


Seagate Research.ppt



Information the way you want it...

Disk Architecture / Density Potential





Use Locking pattern as Servo Pattern Scalable Density --> 1 Particle per Bit

Thermal Limit: 20 - 100 Tbit/in²

SEAGATE CONFIDENTIAL

Seagate.

Information the way you want it...